



Fabric Backed Tape

Technical Data Sheet

DESCRIPTION

4EvaSeal™ Fabric Tape is a easy to use economical and permanent sealing tape that bonds to most materials, including roofing membranes, metals, plastics, and most other materials. This tape uses an elastomeric adhesive bonded to a woven polyester fabric backing for maximum conformability. 4EvaSeal™ Fabric Tape can be used to seal leaking joints, seams, and cracks. It is designed to expand and contract without any cracking within normal roofing temperatures. 4EvaSeal™ Fabric Tape is not designed for direct exposure to UV, but can be coated or painted with a UV resistant coating.

RECOMMENDED USE

4EvaSeal™ Fabric Tape is designed for sealing joints and seams where top coating is desired. It is ideal for metal buildings, mobile homes, manufactured housing, travel trailers, RV's, utility trailers, and semi-trailers. It can be used to seal skylights, metal roof seams, flashings, penetrations, tears, fountains, tanks, planters, plaza decks, etc.

4EvaSeal™ Fabric Tape may also be used as a detail material with other waterproofing and coating systems.

SUBSTRATE COMPATIBILITY

4EvaSeal™ Fabric Tape will bond aggressively to most materials, including: metals, plastics, roofing materials, wood, gypsum, concrete, brick, fiberglass and many previously painted surfaces. Perform adhesion test to confirm compatibility when required.

SURFACE PREPARATION

Surface must be clean and dry, with no oils, grease or loose debris. Remove salt and other contaminants by pressure washing with a suitable detergent followed by a fresh water rinse. Rust and other adhered foreign matter should be removed by scraping or wire brushing followed by a solvent wipe.

APPLICATION

Center the 4EvaSeal™ Fabric Tape over the seam, removing the plastic release liner gradually to prevent contamination of the adhesive prior to application. This material may be applied to clean dry surfaces above 40° F. For exposed applications a UV resistant coating should be applied over the tape to protect it from UV degradation. Topcoats can be applied directly to the fabric backing.

OPTIONAL PRIMER

All 4EvaSeal™ tapes have an aggressive adhesive to allow for quick, easy and permanent adhesion. When applying to hard to clean surfaces or in cold temperatures (below 40° F), 4EvaSeal™ Primer may be applied to the surface to improve bond.

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.

Chase Corporation
295 University Avenue
Westwood, MA 02090
Phone: 800-323-4182
Fax: 781-332-0701
www.chasecorp.com
An ISO 9001:2008
REGISTERED COMPANY



Typical Technical Data

Property	US Customary	Metric	Test Method
Total Thickness	30 mils	0.76 mm	ASTM D1000
Backing Thickness	11 mils	0.28 mm	ASTM D1000
Adhesive Thickness	19 mils	0.48 mm	ASTM D1000
Adhesion to Metal	12 lb/in	2.10 N/mm	ASTM D1000
Adhesion to Wood	8 lb/in	1.40 N/mm	ASTM D1000
Adhesion to TPO	8 lb/in	1.40 N/mm	ASTM D1000
Tensile Strength	15 lb/in	2.63 N/mm	ASTM D1000
Elongation	100%	100%	ASTM D1000
Water Vapor Transmission Rate @100°F (38°C)	<0.005 g/(24h*100 in ²)	<0.003 g/(h*m ²)	ASTM E96 Procedure B
Water Absorption (adhesive)	<0.5%	<0.5%	ASTM D570
Application Temperature Range*	-20°F to +140°F	-29°C to +60°C	
Service Temperature Range	-20°F to +140°F	-29°C to +60°C	

*Primer recommended below 40°F.

ORDERING INFORMATION

4EvaSeal™ Fabric Backed Tape

Roll Size	Rolls Per Case
2" x 50'	6
4" x 50'	3
6" x 50'	2
12" x 50'	1

CASE PACKAGING

.5 SQ (50 ft²) per case
Case Weight: 17 lbs