



MH20 FLEX-CORD FABRIC CONCRETE PLACEMENT



Application:

General applications are concrete placement, wet gunning, plastics, shot crete, and grout hose at high-pressure.

Construction:

Tube - Black, abrasion resistant synthetic rubber for maximum resistance

Reinforcement - Synthetic yarn

Cover - Black, wrapped finish with a white stripe

Branding - FLEXTRAL MH20-200 2" FLEX-CORD CONCRETE PLACEMENT 1200 PSI MAX WP 5.0 LBS/FT

Temperature Range:

-30°C to +85°C (-22°F to +185°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight lbs / ft	Standard Lengths
MH20-100	1	1.57	1,200	0.58	100'
MH20-125	1¼	1.93	1,200	0.78	100'
MH20-150	1½	2.31	1,200	1.18	100'
MH20-200	2	2.83	1,200	1.55	100'
MH20-250	2½	3.39	1,200	1.97	100'
MH20-300	3	3.94	1,200	2.48	100'
MH20-350	3½	4.65	1,200	3.41	100'
MH20-400	4	5.11	1,200	3.79	100'
MH20-500	5	6.10	1,200	5.11	100'

MH20 FLEX-CORD FABRIC PLACEMENT ASSEMBLIES

Part No.	Hose Size & Length	End 1	End 2	Attaching Method
MH20-150MMIE050-CS	1½" x 50'	M-NPT	M-NPT	Internally Expanded
MH20-150GGIE050-CS	1½" x 50'	Grooved	Grooved	Internally Expanded
MH20-200MMIC050-HS	2" x 50'	M-NPT	M-NPT	Full Flow Crimp
MH20-200HDHDIC050-HS	2" x 50'	Heavy-Duty	Heavy-Duty	Full Flow Crimp
MH20-200GGIC050-HS	2" x 50'	Grooved	Grooved	Full Flow Crimp
MH20-300HDHDIC025-HS	3" x 25'	Heavy-Duty	Heavy-Duty	Full Flow Crimp
MH20-300GGIC025-HS	3" x 25'	Grooved	Grooved	Full Flow Crimp
MH20-400HDHDIC012-HS	4" x 12'	Heavy-Duty	Heavy-Duty	Full Flow Crimp
MH20-400GGIC012-HS	4" x 12'	Grooved	Grooved	Full Flow Crimp
MH20-500HDHDIC012-HS	5" x 12'	Heavy-Duty	Heavy-Duty	Full Flow Crimp
MH20-500MEME012-HS	5" x 12'	Metric	Metric	Full Flow Crimp

*Call for additional fittings, lengths and assemblies.

**HEAVY-DUTY/
CALIFORNIA RAISED**



GROOVED



**148mm
EUROPEAN METRIC**



MALE PIPE



! WARNING This product can expose you to chemicals, which are known to the State of California to cause cancer or birth defects or other reproductive harm. For more information visit <https://www.p65warnings.ca.gov/>