



## MH62 Industrial Vacuum Hose - Drag

**Application:**

Heavy duty abrasion resistant suction hose for municipal sewer vacuum trucks or handling abrasives such as crushed rock, sand, pea gravel, cement powder, dry fertilizer, iron ore, and grains.

**Construction:**

**Tube** - Polyurethane liner

**Reinforcement** - Rigid PVC helix

**Cover** - Thermoplastic alloyed blend of polyurethane and PVC

**Temperature Range:**

-40°C to +65°C (-40°F to +150°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. @70°F	Bend Radius Inches @70°F	Vacuum Inches Hg. @70°F	Weight lbs / ft	Standard Lengths
MH62-150	1½	1.87	40	3.0	Full	0.39	100'
MH62-200	2	2.40	40	2.0	Full	0.59	100'
MH62-250	2½	3.07	40	4.0	Full	0.79	100'
MH62-300	3	3.64	40	4.0	Full	0.83	100'
MH62-400	4	4.76	35	6.0	Full	1.37	100'
MH62-500	5	5.69	30	10.0	28.0	2.28	100'
MH62-600	6	6.81	30	12.0	28.0	3.10	100'
MH62-800	8	9.02	30	15.0	28.0	4.51	50'/20'

\*Call for additional fittings, lengths and assemblies.